

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

BRONTEE

PRODUCT CODE
ŠIFRA PROIZVODA

NB12101



TEHNIČKI PODACI

Dvoručna baterija
Zidna montaža
Flühs® LIFETIME keramički gornji delovi
Metalni rukohvat
Ručni prebacivač
Specijalna Brontee završna obrad
Duplo pleteno tuš crevo 1.5m
Metalna tuš ručica
Heavy Duty ekscentar kolena

TECHNICAL DETAILS

Two handle mixer
Wall mounted
Flühs® LIFETIME ceramic head parts
Metal handle
Manual diverter
Special Brontee finish
Double lock shower hose 1.5m
Solid brass hand shower
Heavy Duty eccentric connectors

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

