

# SPECIFICATION SHEET

## TEHNIČKI LIST



COLLECTION  
SERIJA

# STOLZ WHITE

PRODUCT CODE  
ŠIFRA PROIZVODA

**137251W**



### TEHNIČKI PODACI

Jednoručna baterija  
Montaža na zid  
Klasa protoka 9lit/min  
Tuš ruža D.220mm sa zglobom  
Keramički mešač KEROX® 35 OP HWS  
Automatski prebacivač NEOPERL® CDV-18  
Easy Clean STOLZ tuš ručica  
STOLZ duplo pleteno tuš crevo 150cm  
HD ekscentar kolena 48mm sa utišivačem

### RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

### TECHNICAL DETAILS

Single lever mixer  
Wall assembly  
Flow rate 9 lit/min  
Shower rose D.220mm with knob  
Ceramic cartridge KEROX® 35 OP HWS  
Automatic diverter NEOPERL® CDV-18  
Easy Clean STOLZ hand shower  
STOLZ double locked shower hose 150cm  
HD 48mm eccentric connectors with silencer

### WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C

email : [info@rosan.rs](mailto:info@rosan.rs)

[www.rosan.rs](http://www.rosan.rs)

