

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

S2

PRODUCT CODE
ŠIFRA PROIZVODA

233101



TEHNIČKI PODACI

Jednoručna baterija

Minimalistički dizajn

Telo od mesinga

Hromirana završna obrada

Židna montaža

NEOPERL® HYBRID prebacivač- PREB133

NEOPERL® CASCADE® SLC® - PPM24SLC

Keramički mešač KEROX® 35mm - PKM35A

SILVERFLEX tuš crevo 170cm - PGC170SF

Tuš ručica 3 Funkcije - PTR3C13

RADNI USLOVI

Maksimalni radni pritisak: 5 bar

Preporučeni radni pritisak: 3 bar

Minimalni radni pritisak: 1 bar

Maksimalna dozvoljena temperatura: 70°C

Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer

Minimalist design

Solid brass body

Chrome finish

Wall fixing

NEOPERL® HYBRID shower diverter - PREB133

NEOPERL® CASCADE® SLC® - PPM24SLC

KEROX®35 mm ceramic cartridge - PKM35A

SILVERFLEX shower hose 170cm - PGC170SF

3 Function hand shower - PTR3C13

WORKING CONDITIONS

Max. working pressure : 5 bar

Suggested working pressure : 3 bar

Min. working pressure : 1 bar

Max. working temperature : 70°C

Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

