

COLLECTION  
SERIJA

# NOSTLAGIJA

PRODUCT CODE  
ŠIFRA PROIZVODA

**N22102**



## TEHNIČKI PODACI

Dvoručna baterija  
Montiranje na jedan otvor  
Klasa protoka S  
NEOPERL® PERLATOR® HONEYCOMB  
Flühs® LIFETIME keramički gornji delovi  
Metalni rukohvat  
ROMA, rustični izliv  
INOX set za pričvršćenje  
IMQ sertifikovana fleksibilna priključna creva

## RADNI USLOVI

Maksimalni radni pritisak: 5 bar  
Preporučeni radni pritisak: 3 bar  
Minimalni radni pritisak: 1 bar  
Maksimalna dozvoljena temperatura: 70°C  
Preporučena temperatura vode: 50°C

## TECHNICAL DETAILS

Two handle mixer  
Single hole mounted  
Flow class S  
Aerator NEOPERL® PERLATOR® HONEYCOMB  
Flühs® LIFETIME ceramic head parts  
Metal handle  
Rustical ROMA spout  
Stainless Steel rapid instalation set  
IMQ certified flexible connection hoses

## WORKING CONDITIONS

Max. working pressure : 5 bar  
Suggested working pressure : 3 bar  
Min. working pressure : 1 bar  
Max. working temperature : 70°C  
Suggested max. water temperature : 50°C