

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

STEEL

PRODUCT CODE
ŠIFRA PROIZVODA

JS38603



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Telo od nerđajućeg čelika AISI 304
Ručica od nerđajućeg čelika AISI 304
Klasa protoka C
NEOPERL® PERLATOR® HONEYCOMB
Izvlačno tuš crevo od nerđajućeg čelika
Keramički mešač KEROX® 35 HWS
Povlačni teg 400gr
Pokretni izliv 360°
EASY set za pričvršćenje
IMQ sertifikovana fleksibilna priključna creva

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Single hole assembly
Stainless steel AISI 304 body
Stainless steel AISI 304 lever
Flow class C
Aerator NEOPERL® PERLATOR® HONEYCOMB
Stainless steel pull-out shower hose
Ceramic cartridge KEROX® 35 HWS
Pull-down weight 400 gr.
Swivel spout 360°
Stainless Steel EASY instalation set
IMQ certified flexible connection hoses

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

