

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

ZERRO

PRODUCT CODE
ŠIFRA PROIZVODA

JZ38601



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka S
Keramički mešač KEROX® 35 HWS
Tuš ručica sa prebacivačem
Pleteno izvlačno tuš crevo
INOX set za pričvršćenje
IMQ sertifikovana fleksibilna priključna creva

TECHNICAL DETAILS

Single lever mixer
Single hole mounted
Flow class S
Ceramic cartridge KEROX® 35 HWS
Pull-out shower with diverter
Braided pull-out shower hose
Stainless Steel rapid instalation set
IMQ certified flexible connection hoses

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

