

SPECIFICATION SHEET

TEHNIČKI LIST



COLLECTION
SERIJA

ZERRO

PRODUCT CODE
ŠIFRA PROIZVODA

JZ38901



TEHNIČKI PODACI

Jednoručna baterija
Montiranje na jedan otvor
Klasa protoka C
NEOPERL® PERLATOR® HONEYCOMB
Keramički mešač KEROX® 35 HWS
FLEXibilni izliv sa oprugom
Pokretni izliv 360°
INOX set za pričvršćenje
IMQ sertifikovana fleksibilna priključna creva

RADNI USLOVI

Maksimalni radni pritisak: 5 bar
Preporučeni radni pritisak: 3 bar
Minimalni radni pritisak: 1 bar
Maksimalna dozvoljena temperatura: 70°C
Preporučena temperatura vode: 50°C

TECHNICAL DETAILS

Single lever mixer
Single hole mounted
Flow rate C
NEOPERL® PERLATOR® HONEYCOMB
Ceramic cartidge KEROX® HWS 35 mm
FLEXible spout with spring
Swivel spout 360°
Stainless Steel rapid instalation set
IMQ certified flexible connection hoses

WORKING CONDITIONS

Max. working pressure : 5 bar
Suggested working pressure : 3 bar
Min. working pressure : 1 bar
Max. working temperature : 70°C
Suggested max. water temperature : 50°C

email : info@rosan.rs

www.rosan.rs

